



DESSALATOR SPECIFICATION SHEET

D200 PRO AUTO in 230 or 400V

Application: Intensive use

Versions :

- Remote control with:
Vertical front panel: L 22 cm x H 43 cm x D 12 cm (separated electric box)
High pressure motor unit 2,2 KW: L 55cm x W 33 x H 30
- compact
ABS frame in L: L 58 cm x H 38 cm x D 48 cm

Elements of the water maker:

- Basket pre filter:
brass pre filter (directly installed on the hull valve)
- Low pressure pump: 300 Watts (to be installed under the water line) with a condenser 12.5 Micro farads (except threephased model)
- Double pre filtration container with rinsing solenoid valve: filters in 10 inches, 25 and 5 microns, H 36cm x W 36cm x D 18 cm and key for the pre filter
- High pressure motor unit: 2.2 KW with 2 condensers 2x30 Mfds parallel or 1 condenser of 60 Micro farads (except three-phased model), start soft and 170 Microfarad capacitor
- 1 membrane unit (25.40 membrane) – Dimensions : L 120 cm x 27 x 12 cm including three tubes, three membranes, 2 flasks, 1 full membrane end cap fitting with segment, 2 full membrane end cap fittings, 1 tapped membrane end cap fitting with segment and two tapped membrane end cap fittings, 8 straps, 2 interconnectors, screws.
- Front panel
- Electric box (fixed behind the front panel) with electronic controller (except vertical front panel)
- Manometers (high and low pressure) fixed behind the front panel
- Graduated flowmeter (fixed behind the front panel)
- Pressure captor
- Analyse probe
- Operating time meter
- 3 indicator lights
- Motorization system of the regulating valve
- Mini remote control standard

Supplied accessories:

- Hull valve with strainers in $\frac{3}{4}$
- High pressure hoses \varnothing 8mm – 8 m
- 2 mounted high pressure connectors and 2 to be mounted (with adaptor)
- Capillary hose \varnothing 4mm - 6m
- Blue production hose \varnothing 8/10mm : 6m
- Replacement filters 25 and 5 microns (1 of each)

Consumption, pre pump included:

230V: 15 A continuously. A D 25A circuit breaker is supplied. Cable: 3x2,5mm²
400V: 10 A continuously. A D 16A circuit breaker is supplied. Cable: 4x2,5mm²

Working pressure: Between 60 and 65 Bars. Dessalator manometer with green zone (model registred)

Weight: 76 kg, boxed up: 120 kg